



HOW TO CHOOSE THE RIGHT NAVIGATION LIGHTS					
VESSEL SIZE	NAV.LIGHT SERIES	MODEL	WATTAGE	VOLTAGE	VISIBILITY
<12m/39ft	SERIES 20	Side mount starboard/port	5W	12V	1NM
<12m/39ft	SERIES 20	Side mount starboard/port	5W	12V	1NM
<12m/39ft	SERIES 20	Deck mount starboard/port/bicolor	5W	12V	1NM
<12m/39ft	SERIES 20	Deck mount masthead	5W	12V	2NM
<12m/39ft	SERIES 20	Side mount stern	5W	12V	2NM
<12m/39ft	SERIES 20	Pedestal	5W	12V	2NM
<12m/39ft	SERIES 20	Fold down	5W	12V	2NM
<12m/39ft	SERIES 20	Plug-in	5W	12V	2NM
<12m/39ft	SERIES 25 STANDARD	Side mount starboard/port	10W	12V	1NM
<12m/39ft	SERIES 25 STANDARD	Side mount bicolor/masthead	10W	12V	1NM/2NM
<12m/39ft	SERIES 25 CLASSIC	Side mount starboard/port/bicolor	10W	12V	1NM
<12m/39ft	SERIES 25 CLASSIC	Mast masthead/foredeck combi.	10W/20W	12V	2NM
<20m/65ft	SERIES 34 (LED)	Deck-mount or under step bicolor	3W	10-30V	2NM
<20m/65ft	SERIES 34 (LED)	Deck-mount all around white	1W	10-30V	2NM
<20m/65ft	SERIES 34 (LED)	Deck mount all around red	1,3W	10-30V	2NM
<20m/65ft	SERIES 34 (LED)	Deck mount all around green	1W	10-30V	2NM
<20m/65ft	SERIES 40	Side mount bicolor	25W	12 or 24V	2NM
<20m/65ft	SERIES 40	Side mount masthead	25W	12 or 24V	3NM

HOW TO CHOOSE THE RIGHT NAVIGATION LIGHTS

VESSEL SIZE	NAV.LIGHT SERIES	MODEL	WATTAGE	VOLTAGE	VISIBILITY
<20m/65ft	SERIES 40	Deck-mount masthead/anchor comb.	25/10W	12 or 24V	3/2NM
<20m/65ft	SERIES 40 Sail boat	Deck-mount tricolor and tric. Quickfits	25W	12 or 24V	2NM
<20m/65ft	SERIES 41	Side-mount bicolor	25W	12 or 24V	2NM
<20m/65ft	SERIES 41	Side-mount masthead	25W	12 or 24V	3NM
<20m/65ft	SERIES 50	Side-mount bicolor	25W	12 or 24V	2NM
<20m/65ft	SERIES 50	Side-mount masthead	25W	12 or 24V	3NM
<20m/65ft	SERIES 50	Side-mount stern and stern yellow	10W	12 or 24V	2NM
<20m/65ft	SERIES 50	Deck-mount all around white/ordinary	10W	12 or 24V	2NM
<20m/65ft	SERIES 50	Deck-mount all around white hell	25W	12 or 24V	2NM
<20m/65ft	SERIES 50	Deck-mount all around red,green,yellow	25W	12 or 24V	2NM
<20m/65ft	SERIES 50	Hoistable all around white/white ordinary	10W	12 or 24V	2NM
<20m/65ft	SERIES 50	Hoistable all around white hell	25W	12 or 24V	2NM
<20m/65ft	SERIES 50	All around red/yellow/blue	25W	12 or 24V	2NM
12-<50m/39-164ft	SERIES 20	Pedestal all around white	5W	12V	2NM
12-<50m/39-164ft	SERIES 20	Fold down all around white	5W	12V	2NM
12-<50m/39-164ft	SERIES 20	Fold down masthead	5W	12V	2NM
12-<50m/39-164ft	SERIES 20	Plug-in all around white	5W	12V	2NM
<50m/164ft	SERIES 25 STANDARD	Side-mount stern	10W	12V	2NM
<50m/164ft	SERIES 25 STANDARD	Deck-mount all around white/red/green	10/21/21W	12V	2NM
<50m/164ft	SERIES 25 CLASSIC	Side mount stern	10W	12V	2NM
<50m/164ft	SERIES 34 (LED)	Side-mount Starboard/Port/Stern	1,5W	10-30V	2NM
<50m/164ft	SERIES 40	Side-mount Starboard/Port	25W	12 or 24V	2NM

HOW TO CHOOSE THE RIGHT NAVIGATION LIGHTS					
<50m/164ft	SERIES 40	Side-mount Stern/Stern yellow	10W	12 or 24V	2NM
<50m/164ft	SERIES 40	Deck-mount all around white/red/green	10/25/25W	12 or 24V	2NM
<50m/164ft	SERIES 40	Hoistable all around white/red/green	10/25/25W	12 or 24V	2NM
<50m/164ft	SERIES 40	Deck-mount all around white, quickfits	10W	12 or 24V	2NM
<50m/164ft	SERIES 41	Side mount Starboard/Port	25W	12 or 24V	2NM
<50m/164ft	SERIES 41	Side-mount Stern/Stern yellow	10W	12 or 24V	2NM
<50m/164ft	SERIES 50	Side-mount Starboard/Port	25W	12 or 24V	2NM
<50m/164ft	SERIES 50	Side-mount Masthead white stark	25W	12 or 24V	5NM

NOTE: Above information relate to Aqua Signal Navigation Lights

29 Φραγκλίνου Ρούσβελτ, Τ.Θ 50469, 3605 Λεμεσός. Τηλ. 25877933, Φαξ. 25564301

E-mail: mercury@mercury.com.cy <http://www.mercury.com.cy>